=> file jic FILE 'JICST-EPLUS' ENTERED AT 15:53:11 ON 01 OCT 2002 COPYRIGHT (C) 2002 Japan Science and Technology Corporation (JST)

FILE COVERS 1985 TO 24 SEP 2002 (20020924/ED)

THE JICST-EPLUS FILE HAS BEEN RELOADED TO REFLECT THE 1999 CONTROLLED TERM (/CT) THESAURUS RELOAD.

#### => d que 154

L51 (	7174)SEA FILE=JICST-EPLUS ABB=ON SOLID PHASE EXTRACTION/CT OR
	SOLVENT EXTRACTION/CT OR SOLID-LIQUID EXTRACTION/CT
L52 (	14157)SEA FILE=JICST-EPLUS ABB=ON ENZYME ACTIVITY/CT
L53 (	23)SEA FILE=JICST-EPLUS ABB=ON L51 AND L52
L54	11 SEA FILE=JICST-EPLUS ABB=ON (FOOD# OR FEED OR SOLID#) AND L53

#### => file caplus

FILE 'CAPLUS' ENTERED AT 15:53:12 ON 01 OCT 2002 USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT. PLEASE SEE "HELP USAGETERMS" FOR DETAILS. COPYRIGHT (C) 2002 AMERICAN CHEMICAL SOCIETY (ACS)

Copyright of the articles to which records in this database refer is held by the publishers listed in the PUBLISHER (PB) field (available for records published or updated in Chemical Abstracts after December 26, 1996), unless otherwise indicated in the original publications. The CA Lexicon is the copyrighted intellectual property of the American Chemical Society and is provided to assist you in searching databases on STN. Any dissemination, distribution, copying, or storing of this information, without the prior written consent of CAS, is strictly prohibited.

FILE COVERS 1907 - 1 Oct 2002 VOL 137 ISS 14 FILE LAST UPDATED: 30 Sep 2002 (20020930/ED)

This file contains CAS Registry Numbers for easy and accurate substance identification.

CAS roles have been modified effective December 16, 2001. Please check your SDI profiles to see if they need to be revised. For information on CAS roles, enter HELP ROLES at an arrow prompt or use the CAS Roles thesaurus (/RL field) in this file.

### => d que 165

L55	(	816783)SEA I	FILE=CAPLUS	ABB=ON	PLU=ON	?COLUMN?	OR	TUBE	OR	?CYLINDE	ጸ?
L56	•	,	FILE=CAPLUS		PLU=ON	FUNNEL	יז כז <i>וז</i> כ	·π·ɔ			
L57 L58	•	1834774) SEA I 1408922) SEA I						11:			
L59	(	,	FILE=CAPLUS				•		, ,		
VALVE# OR CLOSURE# OR STOPCOCK## OR STOPPER# OR PLUG# OR CORK# OR SPOUT# OR CONDUIT# )											
L60	(	•	FILE=CAPLUS		• •						
L61	(	129) SEA 1	FILE=CAPLUS	ABB=ON	L58 AND	L60					

L62 (		L61 AND (DEVICE# OR APPARAT## OR
L63 (	INSTRUMENT?) 3343)SEA FILE=CAPLUS ABB=ON	EXTRACTION APPARATUS/CT
L64 (	7) SEA FILE=CAPLUS ABB=ON	L63 AND L62
L65	4 SEA FILE=CAPLUS ABB=ON COUNTERCURRENT)/TI	L64 NOT (CHROMATOGRAPHY OR GAS OR
	COONTERCORRENT)/II	
=> d que		·
> a que	5 1/1	
L66 (	816783) SEA FILE=CAPLUS ABB=ON	PLU=ON ?COLUMN? OR TUBE OR ?CYLINDER?
L67 (	12878) SEA FILE=CAPLUS ABB=ON	
L68 (		((L66 OR L67)) (15A)(STOP(W)COCK## OR TOPCOCK## OR STOPPER# OR PLUG# OR CORK#
	OR SPOUT# OR CONDUIT# )	
L69 (	3343) SEA FILE=CAPLUS ABB=ON	EXTRACTION APPARATUS/CT
L70 ( L71	206)SEA FILE=CAPLUS ABB=ON 1 SEA FILE=CAPLUS ABB=ON	
	·	Feed usl
=> d que	e 175	Feed use  ANT = Analyte
L72 (	3932)SEA FILE=CAPLUS ABB=ON	J
L73 (	7944) SEA FILE=CAPLUS ABB=ON	SOVHI FT#
L74 (	2) SEA FILE=CAPLUS ABB=ON	L72 AND L73 L74 AND SOYBEAN/TI  SC, SX = Section cool
L75	1 SEA FILE=CAPLUS ABB=ON	or cross reference
-> c 169	5 or 171 or 175	L72 AND L73 L74 AND SOYBEAN/TI  SC, SX = Section cool or cross reference  17 = Food & Feed chemistry
-> S 10:	0 01 171 01 173	It-Food & Feed
L122	6 L65 OR L71 OR L75	chem; story
=> file	biosis	d
FILE 'BI	OSIS' ENTERED AT 15:53:16 ON 01	OCT 2002
	HT (C) 2002 BIOLOGICAL ABSTRACTS	
FILE COV	/ERS 1969 TO DATE.	·
CAS REGI	STRY NUMBERS AND CHEMICAL NAMES	(CNs) PRESENT
FROM JAN	NUARY 1969 TO DATE.	
RECORDS	LAST ADDED: 25 September 2002 (	20020925/ED)
=> d que	e 184	
L76 (	615768) SEA FILE=BIOSIS ABB=ON	SEXTRACTS OR SSEPARATS
L77 (		?ASSAY? OR DETERMIN? OR SCREEN? OR
τ 70 /	MEASUR? OR DETECT? OR A 139778) SEA FILE=BIOSIS ABB=ON	
L78 ( L79 (	216874) SEA FILE=BIOSIS ABB=ON	ENZYME#(10A)L77 CONTAINER# OR TUBE# OR ?CYLINDER? OR
•	?FUNNEL? OR ?VESSEL?	
L80 ( L81 (	231037)SEA FILE=BIOSIS ABB=ON 2334)SEA FILE=BIOSIS ABB=ON	DEVICE# OR APPARAT## OR INSTRUMENT# L78 AND L79
L82 (	56) SEA FILE=BIOSIS ABB=ON	L81 AND L80
L83 ( L84	16)SEA FILE=BIOSIS ABB=ON 7 SEA FILE=BIOSIS ABB=ON	L76 AND L82 L83 AND (DEVICE# OR BED OR PELLET OR
20.	VISCOMETER)/TI	The same of the sa

=> d que 186

L85 ( 51) SEA FILE=BIOSIS ABB=ON SEPARATORY (3A) FUNNEL#
L86 3 SEA FILE=BIOSIS ABB=ON L85 AND ENZYME#

=> s 184 or 186

L123 10 L84 OR L86

=> file hcaplus

FILE 'HCAPLUS' ENTERED AT 15:53:19 ON 01 OCT 2002 USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT. PLEASE SEE "HELP USAGETERMS" FOR DETAILS. COPYRIGHT (C) 2002 AMERICAN CHEMICAL SOCIETY (ACS)

Copyright of the articles to which records in this database refer is held by the publishers listed in the PUBLISHER (PB) field (available for records published or updated in Chemical Abstracts after December 26, 1996), unless otherwise indicated in the original publications. The CA Lexicon is the copyrighted intellectual property of the the American Chemical Society and is provided to assist you in searching databases on STN. Any dissemination, distribution, copying, or storing of this information, without the prior written consent of CAS, is strictly prohibited.

FILE COVERS 1907 - 1 Oct 2002 VOL 137 ISS 14 FILE LAST UPDATED: 30 Sep 2002 (20020930/ED)

This file contains CAS Registry Numbers for easy and accurate substance identification.

CAS roles have been modified effective December 16, 2001. Please check your SDI profiles to see if they need to be revised. For information on CAS roles, enter HELP ROLES at an arrow prompt or use the CAS Roles thesaurus (/RL field) in this file.

=> d que 189

L87 ( 6759)SEA FILE=HCAPLUS ABB=ON PLU=ON ENZYMES/CT(L) (ANALYSIS OR ANT/RL)

L88 ( 3531)SEA FILE=HCAPLUS ABB=ON PLU=ON EXTRACTION APPARATUS+NT/CT

L89 2 SEA FILE=HCAPLUS ABB=ON PLU=ON L87 AND L88

=> d que 194

L90 ( 5618)SEA FILE=HCAPLUS ABB=ON PLU=ON ANALYTICAL APPARATUS+OLD/CT
L91 ( 6759)SEA FILE=HCAPLUS ABB=ON PLU=ON ENZYMES/CT(L) (ANALYSIS OR
ANT/RL)
L92 ( 51394)SEA FILE=HCAPLUS ABB=ON PLU=ON EXTRACTION+NT/CT
L93 ( 32)SEA FILE=HCAPLUS ABB=ON PLU=ON L91 AND L92
L94 FILE=HCAPLUS ABB=ON PLU=ON L93 AND L90

=> d que 1102

```
L95 (
           6759) SEA FILE=HCAPLUS ABB=ON PLU=ON ENZYMES/CT(L) (ANALYSIS OR
                ANT/RL)
        1021795) SEA FILE=HCAPLUS ABB=ON PLU=ON
                                                 SOLID
L96 (
1.97 (
          51394) SEA FILE=HCAPLUS ABB=ON PLU=ON
                                                 EXTRACTION+NT/CT
             32) SEA FILE=HCAPLUS ABB=ON PLU=ON L95 AND L97
                                                                      ANST = analytical
study
RL=Role
L98 (
              3) SEA FILE=HCAPLUS ABB=ON PLU=ON L96 AND L98
L99 (
L100(
           9931) SEA FILE=HCAPLUS ABB=ON
                                         PLU=ON
                                                 ENZYMES/CT(L)ANST/RL
                                         PLU=ON
L101(
              2) SEA FILE=HCAPLUS ABB=ON
                                                  L99 AND L100
              1 SEA FILE=HCAPLUS ABB=ON
                                         PLU=ON
                                                  L101 AND SOLID/TD
=> d que 1108
           3928) SEA FILE=HCAPLUS ABB=ON PLU=ON ENZYMES/CT(L)ANT/RL
T-103(
          23149) SEA FILE=HCAPLUS ABB=ON PLU=ON
                                                 FOOD ANALYSIS+OLD/CT
L104(
L105(
           4217) SEA FILE=HCAPLUS ABB=ON PLU=ON
                                                 FEED ANALYSIS+OLD/CT
             62) SEA FILE=HCAPLUS ABB=ON
                                         PLU=ON
L106(
                                                 L103 AND (L104 OR L105)
                                         PLU=ON
             14) SEA FILE=HCAPLUS ABB=ON
                                                 L106 AND (APPARATUS OR
L107(
                DEVICE)
L1-08-
              2 SEA FILE=HCAPLUS ABB=ON PLU=ON L107 AND SOLID
                                                                  ANT = Analyte
=> d que 1112
L109(
           3928) SEA FILE=HCAPLUS ABB=ON PLU=ON ENZYMES/CT(L)ANT/RL
            113) SEA FILE=HCAPLUS ABB=ON PLU=ON L109 AND 17/SC, SX
L110(
L111(
             14) SEA FILE=HCAPLUS ABB=ON PLU=ON L110 AND (APPARATUS OR
               _DEVICE)
L112
              4_SEA_FILE=HCAPLUS_ABB=ON_PLU=ON_L111_AND_(EXTRACT?_OR
               ∼DISSOLV? OR WASH?)
```

=> s 189 or 194 or 1102 or 1108 or 1112

L124 10 L89 OR L94 OR L102 OR L108 OR L112 9

=> file wpix

FILE 'WPIX' ENTERED AT 15:53:24 ON 01 OCT 2002 COPYRIGHT (C) 2002 THOMSON DERWENT

FILE LAST UPDATED: 26 SEP 2002 <20020926/UP>
MOST RECENT DERWENT UPDATE 200262 <200262/DW>
DERWENT WORLD PATENTS INDEX SUBSCRIBER FILE? COVERS 1963 TO DATE

- >>> SLART (Simultaneous Left and Right Truncation) is now
   available in the /ABEX field. An additional search field
   /BIX is also provided which comprises both /BI and /ABEX <<</pre>
- >>> The BATCH option for structure searches has been enabled in WPINDEX/WPIDS and WPIX <<<</pre>
- >>> PATENT IMAGES AVAILABLE FOR PRINT AND DISPLAY <<<
- >>> FOR DETAILS OF THE PATENTS COVERED IN CURRENT UPDATES,
  SEE http://www.derwent.com/dwpi/updates/dwpicov/index.html <<<
- >>> FOR A COPY OF THE DERWENT WORLD PATENTS INDEX STN USER GUIDE, PLEASE VISIT:

http://www.stn-international.de/training center/patents/stn guide.pdf <<<

```
>>> FOR INFORMATION ON ALL DERWENT WORLD PATENTS INDEX USER
    GUIDES, PLEASE VISIT:
    http://www.derwent.com/userguides/dwpi guide.html <<<
=> d que 1121
L113( 1080423)SEA FILE=WPIX ABB=ON ?COLUMN? OR TUBE OR ?CYLINDER? OR
                FUNNEL#
            271) SEA FILE=WPIX ABB=ON SOXHLET#
        1066137) SEA FILE-WPIX ABB-ON ?EXTRACT? OR ?SEPARAT?
L115(
       115823) SEA FILE=WPIX ABB=ON L113 (15A) (STOP(W) COCK## OR VALVE# OR
L116(
                CLOSURE# OR STOPCOCK## OR STOPPER# OR PLUG# OR CORK# OR SPOUT#
                OR CONDUIT# )
L117(
           5114) SEA FILE=WPIX ABB=ON (L116 OR L114) (15A) L115
L118(
          28068) SEA FILE=WPIX ABB=ON LIQUID PHASE
             29)SEA FILE=WPIX ABB=ON L117 AND L118
L119(
                                                     DC = perwent Code
             7) SEA FILE=WPIX ABB=ON L119 AND S/DC
                                                             S=Instrumentation,
measuring of
testing
L120(
£121
              1 SEA FILE=WPIX ABB=ON L120 AND MIXED/TI
=>
=> file stnguide
FILE 'STNGUIDE' ENTERED AT 15:53:26 ON 01 OCT 2002
USE IS SUBJECT TO THE TERMS OF YOUR CUSTOMER AGREEMENT
COPYRIGHT (C) 2002 AMERICAN CHEMICAL SOCIETY, JAPAN SCIENCE
AND TECHNOLOGY CORPORATION, AND FACHINFORMATIONSZENTRUM KARLSRUHE
FILE CONTAINS CURRENT INFORMATION.
LAST RELOADED: Sep 27, 2002 (20020927/UP).
=> dup rem 154 1121 1122 1123 1124
FILE JICST-EPLUS' ENTERED AT 15:56:03 ON 01 OCT 2002
COPYRIGHT (C) 2002 Japan Science and Technology Corporation (JST)
FILE 'WPIX' ENTERED AT 15:56:03 ON 01 OCT 2002
COPYRIGHT (C) 2002 THOMSON DERWENT
FILE 'CAPLUS' ENTERED AT 15:56:03 ON 01 OCT 2002
USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.
PLEASE SEE "HELP USAGETERMS" FOR DETAILS.
COPYRIGHT (C) 2002 AMERICAN CHEMICAL SOCIETY (ACS)
FILE 'BIOSIS' ENTERED AT 15:56:03 ON 01 OCT 2002
COPYRIGHT (C) 2002 BIOLOGICAL ABSTRACTS INC. (R)
FILE 'HCAPLUS' ENTERED AT 15:56:03 ON 01 OCT 2002
USE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.
PLEASE SEE "HELP USAGETERMS" FOR DETAILS.
COPYRIGHT (C) 2002 AMERICAN CHEMICAL SOCIETY (ACS)
PROCESSING COMPLETED FOR L54
PROCESSING COMPLETED FOR L121
PROCESSING COMPLETED FOR L122
PROCESSING COMPLETED FOR L123
PROCESSING COMPLETED FOR L124
L125
             37 DUP REM L54 L121 L122 L123 L124 (1 DUPLICATE REMOVED)
=> d ibib abs 1-37; file home
```

L125 ANSWER 1 OF 37 HCAPLUS COPYRIGHT 2002 ACS 2002:185399 HCAPLUS ACCESSION NUMBER:

DOCUMENT NUMBER:

136:229029

TITLE:

SOURCE:

Method for precipitating mono and multiple layers of

organophosphoric and organophosphonic acids and the

salts thereof in addition to use thereof

Hofer, Rolf; Pawlak, Michael; Textor, Marcus; INVENTOR(S):

Schuermann-Mader, Eveline; Ehrat, Markus; Tosatti,

Samuele

PATENT ASSIGNEE(S):

Zeptosens A.-G., Switz. PCT Int. Appl., 88 pp.

CODEN: PIXXD2

DOCUMENT TYPE:

Patent

LANGUAGE:

German

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

P.F	PATENT NO.		KI	ND DATE				APPLICATION NO.			0.	DATE					
WC	2002	0208	<b></b> 73	 A	2 .	2002	0314		. — .	20	 01-Е	P100	 77	2001	0831		
	W:	ΑE,	AG,	AL,	AM,	ΑT,	ΑU,	AZ,	BA,	BB,	BG,	BR,	BY,	ΒZ,	CA,	CH,	CN,
		CO,	CR,	CU,	CZ,	DE,	DK,	DM,	DZ,	EE,	ES,	FI,	GB,	GD,	GE,	GH,	GM,
		HR,	ΗU,	ID,	IL,	IN,	IS,	JP,	ΚE,	KG,	ΚP,	KR,	ΚZ,	LC,	LK,	LR,	LS,
		LT,	LU,	LV,	MA,	MD,	MG,	MK,	MN,	MW,	MX,	ΜZ,	NO,	NΖ,	PL,	PT,	RO,
		RU,	SD,	SE,	SG,	SI,	SK,	SL,	ТJ,	TM,	TR,	TT,	ΤZ,	UA,	UG,	US,	UZ,
		VN,	YU,	ZA,	ZW,	AM,	ΑZ,	BY,	KG,	ΚZ,	MD,	RU,	ТJ,	TM			
	RW:	GH,	GM,	KE,	LS,	MW,	ΜZ,	SD,	SL,	SZ,	ΤZ,	UG,	ZW,	ΑT,	BE,	CH,	CY,
		DE,	DK,	ES,	FI,	FR,	GB,	GR,	ΙE,	IT,	LU,	MC,	NL,	PT,	SE,	TR,	BF,
		ВJ,	CF,	CG,	CI,	CM,	GΑ,	GN,	GQ,	GW,	ML,	MR,	ΝE,	SN,	TD,	TG	
JA	J 2001	0898	59	Α	5	2002	0322		A	U 20	01-8	9859		2001	0831		
PRIORI	PRIORITY APPLN. INFO.:						CH 2	000-	1732		Α	2000	0905				
WO 2001-EP1										EP10	077	W	2001	0831			

OTHER SOURCE(S): MARPAT 136:229029

The invention relates to a method for pptg. mono or multiple layers of organophosphoric acids of general formula (I(A)) Y-B-OPO3 H2 (IA) or organophosphonic acids of general formula (I(B)) Y-B-PO3 H2 (IB) and the salts thereof, wherein B is an alkyl, alkenyl, alkynyl, aryl, aralkyl, hetaryl or hetaryl alkyl radical and Y is hydrogen or a functional group from the hydroxy, carboxy, amino, optionally low-alkyl- substituted mono or dialkylamino series, thiol, or a neg. acid group from the ester, phosphate, phosphonate, sulfate, sulfonate, maleimide, succinimidyl, epoxy, acrylate series. A biol., biochem. or synthetic indicator element can be coupled to B or Y as addn. or substitution reaction, whereby compds. can also be added imparting on the substrate surface a resistance against protein absorption and/or cell adhesion and in the B chain can be, optionally, composed of one or more ethylene oxide groups rather than one or more CH2 groups. According to the invention, said pptn. occurs on the surfaces of the substrates of pure or mixed oxides, nitrides or carbides of metals and semi-conductors. The invention is characterized in that the water-sol. salts composed of formula (IA) or (IB) are used to treat said surfaces, esp. the surfaces of sensor platforms, implants and medical accessory devices. The invention also relates to the use thereof as part of coated sensor platforms, implants and medical accessory devices in addn. to novel organophosphoric acids and organophosphonic acids themselves. The optionally substituted compds. of general formula (IA) and (IB), wherein the groups B and Y have the above mentioned designations i.e. optionally substituted alkyl, alkenyl, alkynyl, aryl, aralkyl, hetaryl or hetaryl, are equally called organophosphoric acids or phosphonic acids.

L125 ANSWER 2 OF 37 HCAPLUS COPYRIGHT 2002 ACS

ACCESSION NUMBER:

2002:72260 HCAPLUS

DOCUMENT NUMBER:

136:115101

TITLE:

Methods and compositions for rapid protein and peptide

extraction and isolation from cells using a

pore-containing lysis matrix

INVENTOR(S):

Blakesley, Robert W.; Flynn, Barbara; Clausen, Peter

Invitrogen Corporation, USA

PATENT ASSIGNEE(S): SOURCE:

PCT Int. Appl., 83 pp.

CODEN: PIXXD2

DOCUMENT TYPE: LANGUAGE: Patent English

FAMILY ACC. NUM. COUNT:

PATENT INFORMATION:

```
PATENT NO. KIND DATE
                                          APPLICATION NO. DATE
                                                 _____
                         ____
                                           WO 2001-US22080 20010713
     WO 2002006456
                        A1
                                20020124
          W: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
              LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT,
              RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ,
              VN, YU, ZA, ZW, AM, AZ, BY, KG, KZ, MD, RU, TJ, TM
          RW: GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW, AT, BE, CH, CY,
               DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR, BF,
               BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG
     US 2002012982
                         A1 20020131
                                                 US 2001-903864 20010713
     US 2000-218081P P 20000713
US 2001-274630P P 20010312
The present invention relates generally to compns., methods and kits for
PRIORITY APPLN. INFO.:
```

use in extg. and isolating protein or peptide mols. More specifically, the invention relates to such compns., methods and kits that are useful in the isolation of protein or peptide mols. from cells (e.g., bacterial cells, animal cells, fungal cells, viruses, yeast cells or plant cells) via lysis and one or more addnl. isolation procedures, such as one or more filtration and/or chromatog. procedures. In particular, the invention relates to compns., methods and kits wherein protein or peptide mols. are isolated using an integrated pore-contg. lysis/filtration matrix, which may comprise one or more supports (e.g., polyolefin, sintered polyethylene, nitrocellulose, polypropylene, polycarbonate, cellulose acetate, silica, and the like). The compns., methods and kits of the invention are suitable for isolating a variety of forms of protein or peptide mols. from cells. The compns., methods and kits of the invention are particularly well-suited for rapid isolation of recombinant protein or peptide mols. expressed in bacterial cells, either as sol. protein, or as an inclusion body. The invention is particularly useful in high throughput applications, allowing quick isolation and/or anal. of proteins and/or peptides from numerous sources.

REFERENCE COUNT:

3 THERE ARE 3 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L125 ANSWER 3 OF 37 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.

ACCESSION NUMBER: DOCUMENT NUMBER:

2001:324170 BIOSIS PREV200100324170

TITLE:

Process and device for determining the activity of enzymes in liquids, or the

concentration and/or activity of inhibitors in liquids.

AUTHOR(S):

Schumacher, Johannes (1); Werle, Bernd

```
(1) Hildastrasse 9, D-69181 Leimen Germany
CORPORATE SOURCE:
PATENT INFORMATION: US 6171851 January 09, 2001
                   Official Gazette of the United States Patent and Trademark
SOURCE:
                   Office Patents, (Jan. 9, 2001) Vol. 1242, No. 2, pp. No
                   Pagination. e-file.
                   ISSN: 0098-1133.
DOCUMENT TYPE:
                   Patent
LANGUAGE:
                   English
    A process and device are disclosed to determine the
     activity of enzymes in liquids in a largely automatic manner.
     The device for carrying out this process has a column with an
     chromatographic carrier for treating a measurement sample. The carrier is
    mixed with a substance capable of binding to an enzyme inhibitor
    present in the measurement sample and that corresponds to at
    least one enzyme. A measurement sample supply is
     associated to one end of the column. A valve/pump arrangement for filling
     at least one test tube with a carrier and at least part of the
    measurement sample is connected downstream of the column, in the flow
    direction of the measurement sample. The carrier is dissociated into
    cleavage products by the action of the enzyme. The rise in concentration
    per unit of time of at least one of the cleavage products of the carrier
     is sensed during an incubation time. As an alternative or supplementary
     step, the enzyme that corresponds to at least one enzyme
    inhibitor is extracted by chromatography from a
    measurement sample to detect enzyme inhibitors
    in liquids and the thus treated measurement sample is tested for
     inhibitor concentration and/or activity.
L125 ANSWER 4 OF 37 HCAPLUS COPYRIGHT 2002 ACS
                     2001:137466 HCAPLUS
ACCESSION NUMBER:
DOCUMENT NUMBER:
                        134:190327
                        Device and method for determining multiple
TITLE:
                        analytes
                        Abel, Andreas P.; Dubeneck, Gert L.; Ehrat, Markus;
INVENTOR(S):
                        Kresbach, Gerhard M.; Pawlak, Michael;
                        Schurmann-Mader, Eveline
PATENT ASSIGNEE(S):
                        Zeptosens A.-G., Switz.
SOURCE:
                        PCT Int. Appl., 71 pp.
                        CODEN: PIXXD2
DOCUMENT TYPE:
                        Patent
LANGUAGE:
                        German
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:
     PATENT NO.
                 KIND DATE
                                          APPLICATION NO. DATE
     ______
                           -----
                                         -----
                     ----
                                        WO 2000-EP7529 20000803
    WO 2001013096 A1 20010222
        W: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU,
            CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,
            IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,
            MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI,
            SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, AM,
            AZ, BY, KG, KZ, MD, RU, TJ, TM
```

sample containers in a two-dimensional arrangement, which is in contact with the sensor platform directly or through an intermediate sealing medium and which is sealed directly or with the sealing medium is described in which different blochem. or biol. identifying elements for specifically identifying and bonding different analytes are immobilized in .gtoreq.5 discrete measuring areas in a single sample container resp. The measuring areas interact optically with an excitation light from the optical waveguide (e.g., to allow luminescence measurements). Sample or reagent liqs. that were supplied to the sample containers can be removed and other sample or reagent liqs. can then be supplied to the same sample containers, optionally without washing.

REFERENCE COUNT: 10 THERE ARE 10 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L125 ANSWER 5 OF 37 HCAPLUS COPYRIGHT 2002 ACS ACCESSION NUMBER: 2001:850833 HCAPLUS

DOCUMENT NUMBER: 135:368958

TITLE: Quantitative analysis

INVENTOR(S): Noda, Yuichiro; Tanaka, Yoshiyuki; Hirao, Konomu

PATENT ASSIGNEE(S): Arkray, Inc., Japan SOURCE: Eur. Pat. Appl., 43 pp.

CODEN: EPXXDW

DOCUMENT TYPE: Patent LANGUAGE: English

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT,

IE, SI, LT, LV, FI, RO

US 2001055784 Al 20011227 US 2001-858986 20010516
PRIORITY APPLN. INFO.: JP 2000-146498 A 20000518

AB Amts. of components in a specimen can be analyzed with excellent quantitativitý. The anal. comprises: measuring an amt. of a component to be analyzed in a specimen; measuring an amt. of a std. component present

be analyzed in a specimen; measuring an amt. of a std. component present originally and homeostatically in the specimen other than the component to be analyzed; detg. the amt. of the specimen from the amt. of the std. component thus measured and a known concn. of the std. component in the specimen; and detg. a concn. of the component to be analyzed in the specimen from the amt. of the specimen thus detd. and the amt. of the component to be analyzed thus measured. The quant. anal. of the present invention allows a component to be analyzed to be measured with high quantitativity.

L125 ANSWER 6 OF 37 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.

ACCESSION NUMBER: 2001:561559 BIOSIS DOCUMENT NUMBER: PREV200100561559

TITLE: Multiplexed enzyme assays in capillary

electrophoretic single-use microfluidic devices.

AUTHOR(S): Xue, Qifeng (1); Wainright, Ann; Gangakhedkar, Surekha;

Gibbons, Ian

CORPORATE SOURCE: (1) ACLARA BioSciences, Inc., Mountain View, CA:

qxue@aclara.com USA

SOURCE: Electrophoresis, (October, 2001) Vol. 22, No. 18, pp.

4000-4007. print. ISSN: 0173-0835.

DOCUMENT TYPE: Article LANGUAGE: English

U~8

SUMMARY LANGUAGE: English

We describe a method of performing multiple enzyme assays in a single reaction vessel. The resolving power of capillary electrophoresis enables several enzyme assays to be analyzed at high speed in microfluidic arrays. Multiplexed measurement can increase throughput significantly without requiring highly dense microfluidic arrays. Enzyme assays in a multiplexed format for selected kinases in this work show essentially identical performance to assays performed individually. This establishes an approach for screening one compound against multiple enzyme targets simultaneously. Another potential application for performing multiplexed enzyme assay is to study protein-protein (especially enzymeenzyme) interaction by monitoring the enzymatic activity changes.

L125 ANSWER 7 OF 37 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.

ACCESSION NUMBER: DOCUMENT NUMBER:

2002:95819 BIOSIS PREV200200095819

TITLE:

Effectiveness of an ultrafiltration device for use with the enzyme-hydrolysed protein method for determining endogenous ileal nitrogen and amino

acid excretion in the pig.

AUTHOR(S):

Hodgkinson, Suzanne M. (1); Moughan, Paul J.

CORPORATE SOURCE:

(1) Instituto de Produccion Animal, Universidad Austral de

Chile, Valdivia: shodgkin@uach.cl Chile

SOURCE:

Journal of the Science of Food and Agriculture, (December,

2001) Vol. 81, No. 15, pp. 1592-1596. print.

ISSN: 0022-5142.

DOCUMENT TYPE:

Article English

LANGUAGE: The aim of the work was to perform an in vitro study to determine the effectiveness of Centriprep-10 concentrator devices for use with the enzyme-hydrolysed protein method for the determination of endogenous ileal nitrogen and amino acid flows. Different amounts of enzyme-hydrolysed casein (EHC) were added to tubes containing digesta collected from pigs that had received a protein-free diet for 5-8 days. The samples were centrifuged and then ultrafiltered using Centriprep-10 concentrators. The precipitate from the centrifugation step was added to the retentate from the ultrafiltration, and this material was analysed for nitrogen and amino acids. The

ultrafiltrates were also analysed for nitrogen. The amount of nitrogen that was deemed to have originated from the EHC and remained in the precipitate plus retentate fraction of digesta after processing, expressed as a percentage of the total amount of nitrogen added to the tubes as EHC, ranged from 1.0 to 5.0%. The overall mean amounts of amino acid in the precipitate plus retentate fractions originating from the EHC, expressed as a percentage of the amino acids added to the tubes as EHC, ranged from 2.4 to 5.8%. The results demonstrate that with Centriprep-10 concentrators there is a less than complete separation of nitrogen and amino acids originating from EHC from endogenous material in digesta, but for most amino acids this is unlikely to be due to binding of the amino acids to digesta. The incomplete separation of EHC from the endogenous fraction of digesta by Centriprep-10 concentrators may lead to a small overestimation (approximately 2%) of endogenous ileal nitrogen and amino acid flows.

L125 ANSWER 8 OF 37 HCAPLUS COPYRIGHT 2002 ACS ACCESSION NUMBER:

DOCUMENT NUMBER:

2002:127117 HCAPLUS 136:324271

TITLE:

Analytical method of measuring tea catechins in human

plasma by solid-phase extraction and HPLC

with electrochemical detection

AUTHOR(S): Umegaki, Keizo; Sugisawa, Ayako; Yamada, Kazuhiko;

Higuchi, Mitsuru

CORPORATE SOURCE: The National Institute of Health and Nutrition, Tokyo,

162-8636, Japan

SOURCE: Journal of Nutritional Science and Vitaminology

(2001), 47(6), 402-408 CODEN: JNSVA5; ISSN: 0301-4800

PUBLISHER: Center for Academic Publications Japan

DOCUMENT TYPE: Journal LANGUAGE: English

An anal. method for measuring tea catechins in plasma by solid -phase extn. (SPE), followed by HPLC with a coulometric electrochem. detector was developed. The plasma was mixed with an equal vol. of acetonitrile to ppt. protein, and catechins in the resulting supernatant were extd. by SPE, using a C18 cartridge. To correct the extn. efficiency, Et gallate was simultaneously added with acetonitrile as an internal std. Plasma samples were treated in microtubes, and evapn. and SPE were performed by the use of a vacuum centrifuge and vacuum manifold for SPE. The use of these instruments allowed the handling of a large no. of samples simultaneously. In this method, (-)-epicatechin (EC), (-)-epicatechin 3-O-gallate (ECg), (-)-epigallocatechin (EGC), (-)-epigallocatechin 3-O-gallate (EGCg), and Et gallate could be detected as a single peak with high sensitivity. For an anal. of the conjugated form of catechins, plasma samples were treated with glucuronidase and sulfatase. Type H-2 .beta.-glucuronidase effectively digested the conjugated forms, and the enzyme also converted EGCq and ECq to their nongallated form. When the concns. of catechins in plasma were analyzed in subjects who took a single dose of catechin liq., the concn. of free EGCg in plasma reached a max. of 300 nM at 1 h after intake; those of the other free form of catechins increased only slightly after the intake. The concn. of total catechins (free + conjugated forms) in plasma increased up to 2 h after the intake.

REFERENCE COUNT:

15 THERE ARE 15 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L125 ANSWER 9 OF 37 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.

ACCESSION NUMBER: 2001:482179 BIOSIS DOCUMENT NUMBER: PREV200100482179

TITLE: Pellet pestle homogenization of agarose gel

slices at 45degreeC for deoxyribonucleic acid

extraction.

AUTHOR(S): Kurien, B. T. (1); Kaufman, K. M.; Harley, J. B.; Scofield,

R. H.

CORPORATE SOURCE: (1) 825 NE 13th Street, Oklahoma City, OK, 73104:

kurienb@omrf.ouhsc.edu USA

Analytical Biochemistry, (September 15, 2001) Vol. 296, No. SOURCE:

2, pp. 162-166. print.

ISSN: 0003-2697.

DOCUMENT TYPE: Article LANGUAGE: English SUMMARY LANGUAGE: English

A simple method for extracting DNA from agarose gel slices is described. The extraction is rapid and does not involve harsh chemicals or sophisticated equipment. The method involves homogenization of the excised gel slice (in Tris-EDTA buffer), containing the DNA fragment of interest, at 45degreeC in a microcentrifuge tube with a Kontes pellet pestle for 1 min. The "homogenate" is then centrifuged for 30 s and the supernatant is saved. The "homogenized"

agarose is extracted one more time and the supernatant obtained is combined with the previous supernatant. The DNA extracted using this method lent itself to restriction enzyme analysis, ligation, transformation, and expression of functional protein in bacteria. This method was found to be applicable with 0.8, 1.0, and 2.0% agarose gels. DNA fragments varying from 23 to 0.4 kb were extracted using this procedure and a yield ranging from 40 to 90% was obtained. The yield was higher for fragments 2.0 kb and higher (70-90%). This range of efficiency was maintained when the starting material was kept between 10 and 300 ng. The heat step was found to be critical since homogenization at room temperature failed to yield any DNA. Extracting DNA with our method elicited an increased yield (up to twofold) compared with that extracted with a commercial kit. Also, the number of transformants obtained using the DNA extracted with our method was at least twice that obtained using the DNA extracted with the commercial kit.

L125 ANSWER 10 OF 37 JICST-EPlus COPYRIGHT 2002 JST

ACCESSION NUMBER:

1020003328 JICST-EPlus

TITLE:

Purification and Characterization of

Glucuronosyltransferase for the Elucidation of

Physiological Role of Saponin in Soybean Plant and the

Breeding of a Value-added Soybean Variety.

AUTHOR:

SHIRAIWA MASAKAZU; KUROSAWA YASUNORI

CORPORATE SOURCE:

Ibaraki Univ., Fac. of Agric.

SOURCE:

Daizu Tanpakushitsu Kenkyu (Soy Protein Research), (2001) vol. 4, pp. 1-10. Journal Code: L0927B (Fig. 8, Tbl. 1,

Ref. 16)

CODEN: DTKEFV; ISSN: 1344-4050

PUB. COUNTRY:

Japan

DOCUMENT TYPE:

Journal; Article

LANGUAGE:

Japanese

STATUS:

New

We solubilized and purified microsomal glucuronosyltransferase from AB soybean, and elucidated its enzymatic properties. A microsome fraction was isolated from germinating soybean seed and treated with various detergents to solubilize the enzyme. The enzyme activity was monitored throughout purification using 14C!-UDP GlcA and soyasapogenol B as substrates. Purification of glucuronosyltransferase was achieved by HiTrap Q, Superdex 200, HiTrap Blue chromatography procedures. This resulted in an enrichment >130-fold relative to the starting homogenate. Purified enzyme was found to require cation for activity. Studies of the substrate specificity of the purified enzyme demonstrated that the specificity for the sugar residue transferred was very high, as no activity was found when UDP-GlcA was replased by other UDP sugars: UDP-Glc and UDP-Gal. Soyasapogenols which are aglycone of soybean saponin are usable acceptors but glycyrrhetinic acid or flavonone is not. These findings suggest that this glucuronosyltransferase was a specific enzyme for UDP-GlcA as donor and soyasapogenols as acceptor, and it was related to biosynthesis of the sugar chain in soybean saponin. This study provides a basis for molecular characterization of key enzyme in saponin biosynthesis in soybean. The isolation of the gene may enable its use in the elucidation of the biosynthesis and physiological role of saponins in soybean. (author abst.)

L125 ANSWER 11 OF 37 HCAPLUS COPYRIGHT 2002 ACS

ACCESSION NUMBER:

2000:144992 HCAPLUS

DOCUMENT NUMBER:

132:207205

TITLE:

Fast measuring device of enzymatic activity

Roberts, Neil; Moores, Janet

INVENTOR(S): PATENT ASSIGNEE(S):

Rhone-Poulenc Animal Nutrition S.A., Fr.

SOURCE: PCT Int. Appl., 16 pp.

CODEN: PIXXD2

DOCUMENT TYPE:

LANGUAGE:

Patent French

FAMILY ACC. NUM. COUNT:

PATENT INFORMATION:

```
PATENT NO.
                    KIND DATE
                                       APPLICATION NO. DATE
    _____
                                       -----
                                                        -----
                                       WO 1999-FR1990 19990816
                   A1 20000302
    WO 2000011136
        W: AE, AL, AU, BA, BB, BG, BR, CA, CN, CU, CZ, EE, GD, GE, HR, HU,
            ID, IL, IN, IS, JP, KP, KR, LC, LK, LR, LT, LV, MG, MK, MN, MX,
            NO, NZ, PL, RO, RU, SG, SI, SK, SL, TR, TT, UA, US, UZ, VN, YU,
            ZA, AM, AZ, BY, KG, KZ, MD, RU, TJ, TM
        RW: GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW, AT, BE, CH, CY, DE, DK,
            ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, BF, BJ, CF, CG,
            CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG
                A1 20000314
A1 20010613
                                    AU 1999-51727 19990816
EP 1999-936736 19990816
    AU 9951727
    EP 1105456
        R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT,
            IE, FI
                                        BR 1999-14294
    BR 9914294
                          20011106
                     Д
                                                        19990816
                                       JP 2000-566393 19990816
                     T2
    JP 2002523038
                          20020730
PRIORITY APPLN. INFO.:
                                     FR 1998-10533
                                                   A 19980819
                                     WO 1999-FR1990 W 19990816
```

The invention concerns a device for the fast measurement of enzymic activity in a solid food comprising (1) a container for receiving the sample to be tested; (2) a reagent particular to the enzyme whereof the activity is to be measured; and (3) a buffer for placing the enzyme in soln.

REFERENCE COUNT:

THERE ARE 4 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L125 ANSWER 12 OF 37 JICST-EPlus COPYRIGHT 2002 JST

ACCESSION NUMBER: 1001046822 JICST-EPlus

TITLE:

Suppression of D-Galactosamine-induced Liver Injury by

Mushrooms in Rats.

AUTHOR:

LEE E W; HE P; KAWAGISHI H; SUGIYAMA K

CORPORATE SOURCE:

SOURCE:

Shizuoka Univ., Shizuoka, Jpn Biosci Biotechnol Biochem, (2000) vol. 64, no. 9, pp.

2001-2004. Journal Code: G0021A (Fig. 3, Tbl. 1, Ref. 12)

CODEN: BBBIEJ; ISSN: 0916-8451

PUB. COUNTRY:

Japan

DOCUMENT TYPE:

Journal; Short Communication

LANGUAGE:

English

STATUS:

New

Six species of edible mushroom were found to suppress D-galactosamineinduced enhancement of plasma alanine and aspartate aminotransferase activities when powdered mushrooms were added to the diet (5%) and fed to rats for 2wk. Grifola frondosa exhibited the most potent effect in a dose-dependent manner. A significant effect was observed only from the water-soluble low-molecular-weight fraction of G. frondosa. The results indicate that several mushrooms possess a protective effect against liver injury induced by D-galactosa-mine. (author abst.)

L125 ANSWER 13 OF 37 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.

ACCESSION NUMBER: DOCUMENT NUMBER:

2001:151064 BIOSIS PREV200100151064

TITLE:

Sonic wave separation of invertase from a dilute solution

to generated droplets.

AUTHOR(S): Tanner, Robert D. (1); Ko, Samuel; Loha, Veara; Prokop,

Ales

CORPORATE SOURCE: (1) Chemical Engineering Department, Vanderbilt University,

Nashville, TN, 37235: rtanner@vuse.vanderbilt.edu USA

SOURCE: Applied Biochemistry and Biotechnology, (Spring, 2000) Vol.

84-86, pp. 1079-1086. print.

ISSN: 0273-2289.

DOCUMENT TYPE: Article
LANGUAGE: English
SUMMARY LANGUAGE: English

It has previously been shown that a droplet fractionation process, simulated by shaking a separatory funnel containing a dilute protein solution, can generate droplets richer in protein than present in the original dilute solution, can generate droplets richer in protein than present in the original dilute solution. In this article, we describe an alternative method that can increase the amount of protein transferred to the droplets. The new method uses ultrasonic waves, enhanced by a bubble gas stream to create the droplets. The amount of protein in these droplets increases by about 50%. In this method, the top layer of the dilute protein solution (of the solution-air interface) becomes enriched in protein when ar is bubbled into the solution. This concentrating procedure is called bubble fractionation. Once the protein has passed through the initial buildup, this enriched protein layer is transferred into droplets with the aid of a vacuum above th solution at the same time that ultrasonic waves are introduced. The droplets are then carried over to a condenser and coalesced. We found that this new method provides an easier way to remove the protein-enriched top layer of the dilute solution and generates more droplets within a shorter period than the separatory funnel droplet generation method. The added air creates the bubbles and carries the droplets, and the vacuum helps remove the effluent airstream from the condenser. The maximum partition coefficient, the ratio of the protein concentration in the droplets to that in the residual solution (approx 8.5), occurred at pH 5.0.

L125 ANSWER 14 OF 37 JICST-EPlus COPYRIGHT 2002 JST

ACCESSION NUMBER: 1010123272 JICST-EPlus

TITLE: Extraction and Properties of 1-Aminocyclopropane-1-

Carboxylate Synthase in Banana Fruit.

AUTHOR: LIU X-J; NAKANO R; KUBO Y; INABA A

CORPORATE SOURCE: Okayama Univ., Okayama

SOURCE: Engei Gakkai Zasshi (Journal of the Japanese Society for

Horticaltural Science), (2000) vol. 69, no. 6, pp. 696-701.

Journal Code: F0626A (Fig. 3, Tbl. 2, Ref. 21)

CODEN: EGKZA9; ISSN: 0013-7626

CODEN: EGKZA9; 1

PUB. COUNTRY: Japan

DOCUMENT TYPE: Journal; Article

LANGUAGE: English STATUS: New

AB The determination of 1-aminocyclopropane-1-carboxylate(ACC) synthase activity is essential in understanding its role in the ethylene biosynthesis during fruit ripening. Because of the high level of soluble tannins, to date, there has been no report on successful determination of banana ACC synthase activity. In this study, we examined the method of Badran and Jones (1965) for the extraction of ACC synthase from banana fruit. The extraction procedure consists of homogenizing the pulp in polyethyleneglycol(PEG)-added buffer, and then washing the homogenate with acetone. This PEG-acetone method gave a high ACC synthase activity. The common extraction method using polyvinylpyrrolidone(PVP) yielded a much lower or no ACC synthase activity. The changes in ACC synthase activity

determined by the PEG-acetone method correlated with changes in ethylene production during ripening. The optimum pH, Km value for substrate S-adenosylmethionine(SAM), and half-life in the presence of SAM for banana ACC synthase were 9.0, 88.MU.M, and 18min respectively. These values were within the range previously reported for ACC synthase in various plant tissues. From these results, we recommend the following extraction method to determine banana ACC synthase activity: freeze the flesh tissue in liquid nitrogen, store it at -80.DEG.C. until use, homogenize the frozen sample in a Waring blender with PEG-added extraction buffer, and later precipitate the enzyme mixture with acetone. (author abst.)

L125 ANSWER 15 OF 37 JICST-EPlus COPYRIGHT 2002 JST

ACCESSION NUMBER: 1000233990 JICST-EPlus

TITLE: Extraction Method by Water followed by Microwave Heating

for Analyzing Sugars in Strawberry Fruits.

AUTHOR: OGIWARA I; OHTSUKA Y; YONEDA Y; SAKURAI K; HAKODA N;

SHIMURA I

CORPORATE SOURCE: Tokyo Univ. Agriculture And Technol., Tokyo

SOURCE: Engei Gakkai Zasshi (Journal of the Japanese Society for

Horticaltural Science), (1999) vol. 68, no. 5, pp. 949-953.

Journal Code: F0626A (Fig. 2, Tbl. 4, Ref. 8)

CODEN: EGKZA9; ISSN: 0013-7626

PUB. COUNTRY: Japan

DOCUMENT TYPE: Journal; Article

LANGUAGE: English STATUS: New

AB The sugar contents of strawberry fruits extracted by the conventional ethanol method were compared with those extracted with water followed by microwave heating. Sucrose, glucose fructose and total sugar contents did not differ significantly between the two methods. The time for the water extraction method required approximately half that needed for the conventional ethanol method. Sugar metabolizing enzymes are inactivated by boiling in a microwave oven. In this method, frozen fruits should be chopped, quickly weighted at a low temperature, and the pieces immediately heated in a microwave oven. After strawberry fruits are heated in a microwave oven, they could be processed at a room temperature. Thus, the water extraction method followed by microwave heating in less time consuming but equally accurate for measuring the concentration and composition of soluble sugars in strawberry fruits. (author abst.)

L125 ANSWER 16 OF 37 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.

ACCESSION NUMBER: 1999:381647 BIOSIS DOCUMENT NUMBER: PREV199900381647

TITLE: Partitioning invertase between a dilute water solution and

generated droplets.

AUTHOR(S): Ko, Samuel; Loha, Veara; Du, Liping; Prokop, Ales; Tanner,

Robert D. (1)

CORPORATE SOURCE: (1) Chemical Engineering Department, Vanderbilt University,

Nashville, TN, 37235 USA

SOURCE: Applied Biochemistry and Biotechnology, (Spring, 1999) Vol.

77-79, No. 0, pp. 501-510.

ISSN: 0273-2289.

DOCUMENT TYPE: Article
LANGUAGE: English
SUMMARY LANGUAGE: English

AB Water droplets or mist occur naturally in the air at seashores. These water droplets carry inorganic and organic substances from the sea to the land via the air, creating fertile land in sandy coastal areas (1). The same phenomenon occurs in an air-fluidized bed bioreactor (2). In an air-fluidized bed reactor, proteins can be transferred from the bioreactor

semisolid bulk phase to an enriched droplet phase. This protein transfer process (droplet fractionation) can be experimentally simulated by shaking a separatory funnel containing a dilute solution of a given protein, which can be an enzyme like invertase. The created droplets become richer in invertase (protein) than that of the original dilute solution. The droplets can then be coalesced by trapping them and recovering the concentrated protein in the new liquid phase. Typically, in such a droplet fractionation process a collected enzyme can be degraded in its ability to catalyze a chemical reaction. In this article, we explore whether the initial solution pH control variable can be adjusted to minimize the decrease of enzyme activity in this process. The protein droplet recovery problem is one in which the recovered amount of desired protein ( enzyme) in the droplet is maximized, subject to the minimization of the enzyme activity loss. The partition coefficient, which is the ratio between the protein concentration in the droplets and the residual solution, is maximized at approx 4.8 and occurs at pH 3.0. Here, the partition coefficient for invertase decreases as the initial solution pH increases, between pH 3.0 and 8.0. Interestingly, the initial solution surface tension seems to be inversely proportional to the partition coefficient. The partition coefficient reaches a maximum value at a surface tension value of approx 63 mN/m at pH 3.0. The enzymatic activity of the initial, the residual, and the droplet solutions all decrease as the bulk solution pH increases. A decrease of enzymatic activity was observed in the residual bulk solution when compared with that in the initial bulk solution at all pH levels. Also, up to 90% of the invertase activity was lost in the droplets when compared to the initial bulk solution.

L125 ANSWER 17 OF 37 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.

ACCESSION NUMBER: 2000:8612 BIOSIS DOCUMENT NUMBER: PREV200000008612

TITLE: Expanded bed adsorption for recovery of patatin

from crude potato juice.

AUTHOR(S): Straetkvern, Knut O. (1); Schwarz, Jurgen G.; Wiesenborn,

Dennis P.; Zafirakos, Elias; Lihme, Allan

CORPORATE SOURCE: (1) Department of Agricultural and Natural Sciences,

Hedmark College, Blaestad, N-2322, Ridabu Norway Bioseparation, (1999) Vol. 7, No. 6, pp. 333-345.

SOURCE: Bioseparation, (1 ISSN: 0923-179X.

DOCUMENT TYPE: Article LANGUAGE: English

SUMMARY LANGUAGE: English An expanded bed adsorption process was used to isolate patatin possessing esterase activity, from a crude juice of potato tubers. Patatin is the major storage protein of potato tubers and is released in ample amounts in the processing effluent during starch milling. We employed mixed mode affinity resins, where the binding depends primarily on the pH, and is almost independent of the ionic strength. From a library of mixed mode chemistries involving both charged and hydrophobic functions, we screened for ligands with binding specificity for patatin. The dynamic binding capacity of two high density (1.4-1.5 g ml-1) patatin-binding agarose-glass resins in response to change of linear velocity (85-230 cm h-1) was tested in packed (25 ml) and expanded (250 ml) column modes. The column operation included a loading step at low expansion; H/Hoapprx1.2. Adsorption from crude juice at pH 7.5, retained patatins up to a breakthrough level of 50%. The eluate fraction at pH 3.5, now effectively stripped from the pigments, provided a 2.5-fold enzyme enrichment and produced 4 g protein per cycle. Column productivity was 122 kAU L-1 h-1. The study, using potato juice as model feedstock, demonstrated the

feasibility of expanded bed-recovery of potentially valuable proteins from plant biomass.

```
L125 ANSWER 18 OF 37 JICST-EPlus COPYRIGHT 2002 JST
ACCESSION NUMBER: 991044389 JICST-EPlus
TITLE:
                       Systematic extraction of useful material from apple juice
                       extraction residue accompanied by weight reduction effect.
                       (Aomori Prefect.u agriculture and forestry division S).
AUTHOR:
                       NAKAMURA SHINGO
                      Hirosaki Univ., Fac. Agriculture and Life Sci., JPN
CORPORATE SOURCE:
                      Nogaku Seimei Kenkyu kara mita Aomoriken Nogyo no Yuisei.
SOURCE:
                      Aomoriken sHiyaku no Met Hakkutsu Jiqyo Hirosaki Daiqaku
                       Nogaku Seimei Kagakubu Hokokusho. Heisei 11nen, (1999) pp.
                       51-52. Journal Code: N19992967 (Fig. 1)
PUB. COUNTRY:
                       Japan
DOCUMENT TYPE:
                       Journal; Commentary
LANGUAGE:
                       Japanese
STATUS:
                      New
L125 ANSWER 19 OF 37 HCAPLUS COPYRIGHT 2002 ACS
                            1998:747656 HCAPLUS
ACCESSION NUMBER:
DOCUMENT NUMBER:
                            130:20059
TITLE:
                            Device for detection of multiple
                            biomolecules and dissolved substances in
                            liquids
INVENTOR(S):
                            Stumpf, Albert
PATENT ASSIGNEE(S):
                            Germany
                            PCT Int. Appl., 31 pp.
SOURCE:
                            CODEN: PIXXD2
DOCUMENT TYPE:
                            Patent
LANGUAGE:
                            German
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:
     PATENT NO.
                        KIND DATE
                                                APPLICATION NO. DATE
     WO 9850774 A1 19981112 WO 1998-EP2625 19980504
          W: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE,
              DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG,
          KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, AM, AZ, BY, KG, KZ, MD, RU, TJ, TM RW: GH, GM, KE, LS, MW, SD, SZ, UG, ZW, AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, BF, BJ, CF, CG, CI,
              CM, GA, GN, ML, MR, NE, SN, TD, TG
                         A1 19981127
     AU 9876526
                                                AU 1998-76526
                                                                    19980504
                               20000223
                                                 EP 1998-924275 19980504
     EP 980515
                          Α1
          R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT,
              IE, SI, FI
     DE 19819857
                          C2
```

A device for detecting biomols. and dissolved substances in liqs., esp. under conditions in which strict sterility is to be obsd., has a sampling system which can be brought into direct contact with the liq. to be analyzed inside a container (i.e., a bioreactor) and an anal. unit. The samples that are collected are brought into contact with a sensor that suitably is specific to the compd. to be analyzed, esp. a biosensor with specific receptors (an antibody, etc.) that can detect the compd. shortly after it is sampled. The device, which can

20000831

PRIORITY APPLN. INFO.:

DE 1998-19819857 19980504 DE 1997-19718828 A 19970505 WO 1998-EP2625 W 19980504

be equipped with further sepn. means (such as dialyzer, membrane filter, etc.), can be conveniently sterilized by exposure to high-temp. steam. The invention can be used in the foodstuff, pharmaceutical and chem. industry, for processes of environmental biotechnol. and prodn. of active substances by means of recombinant cells and enzymes.

REFERENCE COUNT: 8

8 THERE ARE 8 CITED REFERENCES AVAILABLE FOR THIS RECORD. ALL CITATIONS AVAILABLE IN THE RE FORMAT

L125 ANSWER 20 OF 37 HCAPLUS COPYRIGHT 2002 ACS ACCESSION NUMBER: 1998:721463 HCAPLUS

DOCUMENT NUMBER: 129:313096

TITLE: Device and apparatus for the

simultaneous detection of multiple analytes INVENTOR(S): Fitzgerald, Stephen Peter; Lamont, John Victor;

Mcconnell, Robert Ivan; Benchikh, El Ouard

PATENT ASSIGNEE(S): Randox Laboratories Ltd., UK

SOURCE: Eur. Pat. Appl., 26 pp.

CODEN: EPXXDW

DOCUMENT TYPE: Patent LANGUAGE: English

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PA:	TENT NO.		KIN	D DAT	E		AI	PPLI	CATI	ON N	٥.	DATE			
					01000							1000			
EP	874242		A1	199	81028		EE	. 19	98-3	0301	9	1998	)420		
	R: AT,	BE,	CH,	DE, DK	, ES,	FR,	GB,	GR,	ΙΤ,	LI,	LU,	NL,	SE,	MC,	PT,
	IE,	SI,	LT,	LV, FI	, RO										
BR	9800655		Α	199	90810		BF	R 199	98-6	55		1998	0417		
CA	2235183		AA	199	81021		CF	199	98-2	2351	83	1998	0420		
AU	9861988		A1	199	81022		JA	J 199	98-6	1988		1998	0420		
AU	713388		В2	199	91202										
NO	9801766		Α	199	81022		NC	199	98-1	766		1998	0420		
GB	2324866		A1	199	81104		GE	3 199	98-8	309		1998	0420		
GB	2324866		В2	200	11114										
RU	2168174		C2	200	10527		RU	J 199	98-1	0757	1	1998	0420		
JP	10319011	L	A2	199	81204		JE	199	98-1	1068	7	1998	0421		
ZA	9803345		Α	199	90421		ZP	199	98-3	345		1998	0421		
CN	1215167		Α	199	90428		CN	1 199	98-1	1525	4	1998	0421		
PRIORITY	APPLN.	INFO.	:				EP 19	97-3	3027	07	Α	1997	0421		

AB A solid state device for performing multi-analyte assays, comprises a substrate and a multiplicity of discrete reaction sites each bearing a ligand covalently bonded to the substrate, wherein the surface of the substrate between the reaction sites is inert with respect to analyte. Such a device may be obtained by a process of activating the surface of the substrate, and applying an array of ligands on to discrete areas on the surface.

L125 ANSWER 21 OF 37 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.

ACCESSION NUMBER: 1999:247550 BIOSIS DOCUMENT NUMBER: PREV199900247550

TITLE: The effect of pH on the activity of cellulase fractionated

between bulk and droplet phases.

AUTHOR(S): Loha, Veara; Nun, Shuhaida; Sarkawi, Salina; Prokop, Ales;

Tanner, Robert D. (1); Vitolo, Michele

CORPORATE SOURCE: (1) Chemical Engineering Department, Vanderbilt University,

Nashville, TN, 37235 USA

SOURCE: Revista de Farmacia e Bioquimica da Universidade de Sao

Paulo, (1998) Vol. 34, No. 2, pp. 101-107.

ISSN: 0370-4726.

DOCUMENT TYPE: Article
LANGUAGE: English
SUMMARY LANGUAGE: English

AB Aqueous cellulase solutions were vigorously shaked in a separatory funnel, promoting a partition of the enzyme between the droplets formed and the residual bulk solution. The partition coefficient (Kp) was defined as the ratio of protein concentrations in the droplets and in the residual bulk solution. The Kp depended on both initial pH and cellulase concentration, being markedly favoured by using dilute enzyme solutions (up to 40 mg/L) and initial pH between 2.0 and 3.0.

L125 ANSWER 22 OF 37 CAPLUS COPYRIGHT 2002 ACS DUPLICATE 1

ACCESSION NUMBER: 1997:634841 CAPLUS

DOCUMENT NUMBER: 127:277317

TITLE: Response surface analysis of enzyme aided extraction

of soybean

AUTHOR(S): Kashyap, M. C.; Agrawal, Y. C.; Sarkar, B. C.; Singh,

B. P. N.

CORPORATE SOURCE: Department of Process and Food Engineering, G.B. Pant

University of Agriculture and Technology, Pantnagar,

263 145, India

SOURCE: Journal of Food Science and Technology (1997), 34(5),

386-390

CODEN: JFSTAB; ISSN: 0022-1155

PUBLISHER: Association of Food Scientists and Technologists

(India)

DOCUMENT TYPE: Journal LANGUAGE: English

AB Response surface anal. of enzymic hydrolysis of soy flakes was conducted and the parameters optimized to enhance both the extractable oil and the extractability of soy flakes. The optima were at 24.58% wb moisture content, 14.23% v/w enzyme concn. and 13.29 h hydrolysis period. Soy flakes hydrolyzed under optimal conditions had an extractable oil content of 24.93% on moisture-free basis compared to 22.88% in unhydrolyzed flakes and an extractability of 99.83% compared to 82.22% of the extractable oil in 16 h on Soxhlet app. For 99% oil recovery, as practiced com., enzymic hydrolysis reduced the Soxhlet extn. time by over 44% in soy flakes.

L125 ANSWER 23 OF 37 CAPLUS COPYRIGHT 2002 ACS ACCESSION NUMBER: 1997:341596 CAPLUS

DOCUMENT NUMBER: 127:59973

TITLE: Fully automated isolation of natural products
AUTHOR(S): Mellor, Frank; God, Ralf; Bindseil, Kai Uwe; Gumm,

Holger

CORPORATE SOURCE: Merck K.-G.a.A., Darmstadt, D-64271, Germany SOURCE: GIT Spezial Chromatographie (1997), 17(1), 19-22

CODEN: GSCHEP; ISSN: 0940-032X

PUBLISHER: GIT Verlag
DOCUMENT TYPE: Journal
LANGUAGE: German

AB Sepbox, a new, completely automatic chromatog. system has been developed to quickly sep. highly complex mixts. of natural exts. into the pure or almost pure substances; these can then be used directly for biol. testing. The method is a combination of HPLC and solid phase extn. (SPE) and is coupled into a HPLC/SPE/HPLC/SPE unit with 4 semi-preparative pumps, 7 sepg. columns, 28 collecting columns for SPE, >50 valves for column-switching, a light scattering detector and 2 UV detectors for monitoring. The whole system

is controlled by a specially developed software package. An ext. of  $1-5~\rm g$  can be fractionated into 200-300 pure compds. within 24 h. Thus the Sepbox is ideal for delivering samples for high-through-put screening of natural products. Other applications are in the fields of ext. purifn., development of methods for biol. pest control, search for new scents and aromas, as well as biodegradable substances from growing raw materials.

L125 ANSWER 24 OF 37 JICST-EPlus COPYRIGHT 2002 JST

ACCESSION NUMBER: 970173438 JICST-EPlus

TITLE: Role of Proteasome in the Conversion of Muscle to Meat.

AUTHOR: SUZUKI ATSUSHI; IKEUCHI YOSHIHIDE; HONMA NORIYUKI

CORPORATE SOURCE: Niigata Univ., Fac. of Agric.

SOURCE: Shokuniku ni kansuru Josei Kenkyu Chosa Seika Hokokusho,

(1996) vol. 14(1995), pp. 251-255. Journal Code: X0296A

(Fig. 7, Ref. 11)

PUB. COUNTRY: Japan

DOCUMENT TYPE: Journal; Article

LANGUAGE: Japanese STATUS: New

This paper describes the purification and properties of a multi catalytic proteinase complex, proteasome, from rabbit skeletal muscle. Proteasome activities were gradually lost with decreasing pH, but the degree of decrease was substrate-dependent, and activities at pH5.0 still showed about 30-60% of the activity at pH8.0. This indicates the possibility that the proteasome is active in the muscle during ageing. When the proteasome was heated at 60.DEG.C. for 20min and treated in the presence of 0.01% SDS. the activity increased over 1.5 times and 1.6 times, respectively. Proteasome was also activated by the high hydrostatic pressure up to 100MPa and inactivated at 200MPa or higher. Electron microscopic observation revealed that the obvious gap between filaments structure and complete loss of M-line, with partial loss of Z-line were caused by proteasome. These results indicate that proteasome may affect on meat tenderization under high pressure treatment. (author abst.)

L125 ANSWER 25 OF 37 JICST-EPlus COPYRIGHT 2002 JST

ACCESSION NUMBER: 960554291 JICST-EPlus

TITLE: Pectinesterase activity during the Ripening stage from

Strawberry.

AUTHOR: INARI TAEKO; TAKEUCHI TOKUO; TOMOEDA MIKIO CORPORATE SOURCE: Gifu Women's Univ., Fac. of Home Econ.

SOURCE: Gifu Joshi Daigaku Kiyo (Bulletin of Gifu Women's College),

(1996) no. 25, pp. 31-37. Journal Code: Z0746A (Fig. 6,

Tbl. 1, Ref. 10) ISSN: 0286-8644

PUB. COUNTRY: Japan

DOCUMENT TYPE: Journal; Article

LANGUAGE: Japanese STATUS: New

AB Some fruits and vegetables are generally said to become soft by ripening. In this study pectinesterase(E.C.3.1.1.11 PE) activity during the ripening stage from strawberry(Hoko wase) was examined. 1) The activity of the PE did not hardly change with the ripening of strawberry. 2) The activities of the PE were about 1800U/100g fresh weight strawberry. 3) The crude PE from strawberry was purified by salting-out and affinity chromatographic methods. 4) After purification, the relative activities of the separated PE were rised to 33-fold(early ripe), 12-fold(half ripe), 19-fold(over ripe). 5) The molecular weight of the separated PE was estimated about 10,000 by HPLC. 6) The freezing dried PE was in good preservation. (author abst.)

L125 ANSWER 26 OF 37 JICST-EPlus COPYRIGHT 2002 JST

ACCESSION NUMBER: 960655967 JICST-EPlus

TITLE: Genotypic variation in photosynthetic characteristics and

kinetic properties of RuBP carboxylase in \*Triticosecale

AUTHOR: REDDY A R

CORPORATE SOURCE: Pondicherry Univ., Pondicherry, IND

Wheat Inf Serv, (1996) no. 82, pp. 19-23. Journal Code: Y0174A (Tbl. 2, Ref. 13) SOURCE:

ISSN: 0510-3517

PUB. COUNTRY: Japan

DOCUMENT TYPE: Journal; Article

LANGUAGE: English STATUS:

The photosynthetic capacity of single leaves and kinetic properties of RuBP carboxylase were studied among seven genotypes of \*Triticosecale Witt. The photosynthetic rates among the genotypes ranged from 15.7 to 25.8.MU.mol m-2s-1 at an irradiance of 1500.MU.mol quanta m-2s-1. The cultivar 6A-1093 showed the highest rates of CO2 fixation while 6A-854 showed the lowest. The photosynthetic rates were significantly correlated with RuBP carboxylase activities in leaf extracts. There was no apparent difference in the chlorophyll content among the genotypes. The Km and Vmax values for RuBP carboxylase in leaf extracts greatly varied among the genotypes. It was concluded that the variation in the rates of CO2 fixation and kinetic characteristics of RuBP carboxylase among triticale genotypes is important in selection of varieties for improved photosynthetic productivity. (author abst.)

L125 ANSWER 27 OF 37 CAPLUS COPYRIGHT 2002 ACS

ACCESSION NUMBER: 1994:608401 CAPLUS

DOCUMENT NUMBER:

121:208401

TITLE:

Soxhlet extraction apparatus for extracting

nonvolatile components from solid samples by solvents

INVENTOR(S):

Kubo, Satoru Kubota Kk, Japan

PATENT ASSIGNEE(S): SOURCE:

Jpn. Kokai Tokkyo Koho, 4 pp.

CODEN: JKXXAF

DOCUMENT TYPE:

Patent Japanese

LANGUAGE:

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO. KIND DATE APPLICATION NO. DATE \_\_\_\_\_ \_\_\_\_ -----JP 06190205 A2 19940712 JP 1992-359106 19921225

AB The app. comprises a vessel, a cylindrical extn. column having a sample chamber connected to the top opening of the vessel via a vertical path (with valve) under the chamber, and a condenser connected to the top of the column. The app. is used for detn. of crude fats, etc.

L125 ANSWER 28 OF 37 JICST-EPlus COPYRIGHT 2002 JST

ACCESSION NUMBER: 950549374 JICST-EPlus

Extraction of a proteolytic enzyme from the fruit of a TITLE: kiwifruit and utilization to softening of adult chicken

meat.

KAWASHIMA KAZUKO AUTHOR:

CORPORATE SOURCE: Aichi-ken Agric. Res. Cent.

SOURCE: Kanto Tokai Nogyo no Shingijutsu, (1993) no. 10(1993), pp.

307-310. Journal Code: L0587A (Fig. 1, Tbl. 4)

PUB. COUNTRY:

Japan

DOCUMENT TYPE:

Journal; Short Communication

LANGUAGE:

Japanese

STATUS:

New

L125 ANSWER 29 OF 37 CAPLUS COPYRIGHT 2002 ACS

ACCESSION NUMBER: 1993:628638 CAPLUS

DOCUMENT NUMBER:

119:228638

TITLE:

INVENTOR(S):

Extraction, washing, and suspension-separation column Blyakher, Iosif G.; Shterenzon, Aleksandr L.;

Mirkhodzhaev, Mirgani M.; Utabaev, Zafar U.; Gofman, Mikhail S.; Terentev, Vladimir B.; Vajsbejn, Mark M.;

Korostelev, Aleksandr V.

PATENT ASSIGNEE(S): SOURCE:

Ural Scientific-Research Chemical Institue, USSR U.S.S.R. From: Izobreteniya 1992, (34), 25-6.

CODEN: URXXAF

DOCUMENT TYPE: LANGUAGE:

Patent Russian

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

KIND DATE PATENT NO. APPLICATION NO. DATE \_\_\_\_\_ SU 1761178 A1 19920915 SU 1990-4877518 19901024

The column includes a housing, upper and lower settling chambers, media inlets and outlets, and perforated plates. For increasing the process efficiency by increasing the flow of extractant or washing liq. and preventing the piling of solids and for simplifying the column construction, the lower settling chamber has an alternately operated valve, the housing is an assembly of truncated cones connected with greater and smaller bases, and the plates are located at joints of smaller bases.

L125 ANSWER 30 OF 37 HCAPLUS COPYRIGHT 2002 ACS

ACCESSION NUMBER:

1991:403747 HCAPLUS

DOCUMENT NUMBER:

115:3747

TITLE:

Enzyme mass transfer coefficient in aqueous two phase

system using a packed extraction column

AUTHOR(S):

Patil, T. A.; Jafarabad, K. Rostami; Sawant, S. B.;

Joshi, J. B.

CORPORATE SOURCE:

Dep. Chem. Technol., Univ. Bombay, Bombay, 400 019,

India

SOURCE:

Can. J. Chem. Eng. (1991), 69(2), 548-56

CODEN: CJCEA7; ISSN: 0008-4034

DOCUMENT TYPE: LANGUAGE:

Journal English

Fractional dispersed phase hold-up and dispersed side mass transfer coeffs. for amyloglucosidase were measured in a 56 mm i.d. packed extn. column using a sodium sulfate-polyethylene glycol 4000 system. Raschig rings (3 to 13.3 mm), Berl saddles (12 mm), Pall rings (12.6) mm, glass spheres (5.2 mm), and structured wire gauze were used as packings. The effect of packing size was investigated in the case of ceramic Raschig rings. The effect of phase compn. of the aq. phase system also was studied. Correlations have been developed for fractional dispersed phase hold-up and volumetric mass transfer coeff. with packing voidage, dry surface area of packings, superficial dispersed phase velocity, and the liq. phase phys. properties.

L125 ANSWER 31 OF 37 JICST-EPlus COPYRIGHT 2002 JST

ACCESSION NUMBER: 890370869 JICST-EPlus

TITLE: Phosphoenolpyruvate carboxylase level in soybean seed

highly correlates to its contents of protein and lipid. AUTHOR:

SUGIMOTO T; MONMA M; KAWAMURA Y; SAIO K

TANAKA K

National Food Research Inst., Ministry of Agriculture, CORPORATE SOURCE:

Forestry, and Fisheries, Tsukuba, JPN

National Inst. Environmental Studies, Tsukuba, JPN SOURCE: Agric Biol Chem, (1989) vol. 53, no. 3, pp. 885-887. Journal Code: G0021A (Fig. 1, Ref. 12)

CODEN: ABCHA6; ISSN: 0002-1369

PUB. COUNTRY: Japan

DOCUMENT TYPE:

Journal; Short Communication

LANGUAGE: STATUS:

English New

L125 ANSWER 32 OF 37 CAPLUS COPYRIGHT 2002 ACS ACCESSION NUMBER:

DOCUMENT NUMBER:

1987:639228 CAPLUS

107:239228

TITLE:

Automatic solids extraction method and

apparatus with solvent recovery

INVENTOR(S):

Langer, Alfred

PATENT ASSIGNEE(S):

Gerhardt, C., Fabrik und Lager Chemischer Apparate

G.m.b.H. und Co. K.-G., Fed. Rep. Ger.

SOURCE:

Ger. Offen., 8 pp. CODEN: GWXXBX

DOCUMENT TYPE:

Patent

LANGUAGE:

German

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
DE 3710385	A1	19871015	DE 1987-3710385	19870328
DE 3710385	C2	19900913	3.10303	100,0020

For quality control of solid samples, an efficient solvent extn. AΒ is conducted in which the sample is contacted with hot solvent vapor and washed with condensed liq. solvent while the unused solvent is collected and recovered. The app. comprises a sample cage suspended in a solvent bath heated by a heating plate, such that hot solvent vapors rise and contact the sample and also a condenser coil above the solvent bath. A portion of the condensed solvent drips onto and washes the sample while the remainder is automatically directed via a funnel and line through a control valve to a collection vessel.

L125 ANSWER 33 OF 37 CAPLUS COPYRIGHT 2002 ACS ACCESSION NUMBER: 1987:121970 CAPLUS

DOCUMENT NUMBER:

106:121970

TITLE:

Apparatus for solid-liquid extraction and/or reaction INVENTOR(S):

Fancovic, Karol; Stimbranyi, Ladislav; Hauskrecht,

Peter; Cervenka, Zdenek

PATENT ASSIGNEE(S):

SOURCE:

Czech. Czech., 5 pp.

CODEN: CZXXA9

DOCUMENT TYPE: LANGUAGE:

Patent Slovak

FAMILY ACC. NUM. COUNT:

PATENT INFORMATION:

PATENT NO.

KIND DATE

APPLICATION NO. DATE

B1 19850416 CS 1983-6023

A lab. ground-joint glass app. is described for extn. of solids with ligs. at various temps. or for reaction of solids with liqs. The app. consists of a heating section, insulation jacket, extn. and melting sections, a separator, and a condenser. It has a boiling flask with a magnetic stirrer and a gas or extn.-solvent inlet, a heating plate, an evacuated insulation jacket, and an extn. tube contg. the solid material on a fritted-glass plate. The separator for condensate is placed between the extn. tube and the condenser and is connected with a receiver through a valve. The app. can be also made of quartz or Teflon for special purposes.

L125 ANSWER 34 OF 37 JICST-EPlus COPYRIGHT 2002 JST

ACCESSION NUMBER: 860446838 JICST-EPlus

TITLE: Formation of methyl and ethyl .BETA.-D-fructofuranosides in

aqueous methanol and ethanol extracts of Japanese persimmon

fruits.

AUTHOR: HIRAI SHUNJI; ROKUHARA SAYAKA; SHIMIZU SUMIO

CORPORATE SOURCE: Iida Women's Junior College

SOURCE: Nippon Nogei Kagakkaishi (Nippon Nogeikagaku Kaishi),

(1986) vol. 60, no. 7, pp. 521-523. Journal Code: F0231A (Fig. 1, Tbl. 1, Ref. 9)

CODEN: NNKKAA; ISSN: 0002-1407

PUB. COUNTRY: Japan

DOCUMENT TYPE: Journal; Short Communication

LANGUAGE: Japanese STATUS: New

Enzymatic formation of methyl and ethyl .BETA.-D-fructofuranosides was AB investigated in aqueous methanol and ethanol extracts of Japanese persimmon fruits. The fruits were extracted with 60% methanol or 40% ethanol at 20.DEG.C for 24hr. The extracts were concentrated and submitted to Dowex 1X2 (OH) column chromatography, to separate methyl and ethyl .BETA.-D-fructofuranoside for 13C-NMR and polarimetric analysis. The invertase in the persimmon was active considering the high concentration of methanol and ethanol. The formation of .BETA.-D-fructofuranosides in the alcoholic extracts of the fruits was due to the action of invertase. In extraction at 20.DEG.C for 24hr, 40-50% methanol gave 10-15% methyl, and 20% ethanol, 3-6% ethyl .BETA.-D-fructofuranosides, to total mono and oligo saccharides (free sugars). (author abst.)

L125 ANSWER 35 OF 37 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.

ACCESSION NUMBER: 1986:116190 BIOSIS

DOCUMENT NUMBER: BA81:26606

TITLE: A NEW CENTRIFUGAL FILTRATION DEVICE FOR FREE DRUG

SEPARATION.

TROUPIN A S; SHAW L M AUTHOR(S):

TOXICOL. LAB., WILLIAM PEPPER LAB., HOSP. UNIV. PA., CORPORATE SOURCE:

PHILADELPHIA, PA. 19104, USA.

SOURCE: EPILEPSIA, (1985) 26 (5), 455-459.

CODEN: EPILAK. ISSN: 0013-9580.

FILE SEGMENT: BA; OLD LANGUAGE: English

A new centrifugal membrane filtration device (Syva Corporation) has been evaluated to determine its capabilities for separation

of free phenytoin for analysis. The device is a test

tube-size cylinder with two compartments

separated by the membrane. In serum samples from 70 patients at the Hospital of the University of Pennsylvania, free phenytoin was prepared by the new **device** and by equilibrium dialysis. Levels were **assayed** by gas chromatography and **enzyme immunoassay** with good agreement at all phenytoin levels. Although pH has a significant effect on the binding of some drugs to serum proteins, phenytoin binding increased to only a small extent as pH was increased from 7.0 to 7.8 (85-88.5% bound). Centrifugal filtration with this **device** is a reliable, fast, and easy way to prepare free drug from serum and does not include the dilution artifact inherent in equlibrium dialysis.

L125 ANSWER 36 OF 37 WPIX (C) 2002 THOMSON DERWENT

ACCESSION NUMBER: 1

1981-23536D [14] WPIX

TITLE: Liq. phase sampler tube -

with **separate** inlets for organic and aq. phase

and shifting valve cone for mixed

phase.

DERWENT CLASS:

A97 J04 K05 **s03** X14

INVENTOR(S):

ANTONI, H; KLUTH, M; STICH, W

PATENT ASSIGNEE(S):

(GESL) KERNFORSCHUNGSZENT KARLSRUHE

COUNTRY COUNT:

PATENT INFORMATION:

PATE	ON TN	KIND	DATE	WEEK	LA	PG
GB 2 FR 2 US 4 GB 2	933368 060562 463925 348909 060562	A A A B	19810507 19810403 19820914 19830407	(198121) (198239) (198314)		
DE 2	933368	С	19840607	(198424)		

#### APPLICATION DETAILS:

PATENT NO	KIND	APPLICATION	DATE
			<del>-</del>
DE 2933368	A	DE 1979-2933368	19790817

PRIORITY APPLN. INFO: DE 1979-2933368 19790817

AN 1981-23536D [14] WPIX

AB DE 2933368 A UPAB: 19930915

A probe to extract samples of liqs. of the different phases of immiscible substances, e.g. organic, aq. and mixed phase during the reprocessing of nuclear fuel elements by the PUREX process, has a sampler tube which is closed at the end by a plug, made of a coalescence promoting material.

A cavity in the latter has inlet bores, facing in the direction of incidence of the phase concerned. A valve cone of the same material has bores which link the cavity with the inside of the sampler tube.

This enables the organic phase, in particular, to be sampled without adulteration. The probe is small and is suitable for all three phases. DE 2933368 C UPAB: 19930915

Space-saving sampler for partial quantities of liqs. in different phases comprising two immiscible liqs., e.g. organic, aq. and mixed-phase liqs. used in the PUREX reprocessing of nuclear fuels, provides just one structural component to effect clean sepn. of continuous and disperse phases. The sampler, which can be remote controlled, operates without contamination and has a sampling tube with a stopper which is closed to a material that functions as a coalescence aid, comprising a single phase that is taken up by a cavity. The phase proceeding in the direction of flow is met by bore-holes which point in the opposite direction, the

extension of which is sealed off from the tube interior towards the beginning of the tube by a valve cone with the same properties as the stopper. The cavity and/or its extension are connected via bore-holes in the valve cone with the tube interior.

The stainless steel tube may have a stopper made of PTFE or polyethylene.

L125 ANSWER 37 OF 37 BIOSIS COPYRIGHT 2002 BIOLOGICAL ABSTRACTS INC.

ACCESSION NUMBER:

1979:167378 BIOSIS

DOCUMENT NUMBER:

BA67:47378

TITLE:

FLOW THROUGH VISCOMETER FOR USE IN THE AUTOMATED

DETERMINATION OF HYDROLYTIC ENZYME

ACTIVITIES APPLICATION IN PROTEASE AMYLASE AND PECTINASE

AUTHOR(S):

KUIPER J; ROELS J A; ZUIDWEG M H J

CORPORATE SOURCE:

RES. DEV., GIST-BROCADES N.V., DELFT, NETH.

SOURCE:

ANAL BIOCHEM, (1978) 90 (1), 192-203.

CODEN: ANBCA2. ISSN: 0003-2697.

FILE SEGMENT:

BA; OLD English

LANGUAGE:

A flow-through viscometer developed for application as a sensor in automated analysis is described. Its essential part is a glass capillary connected to the sample flow circuit with thin-walled rubber tubes at both ends. These tubes separate the fluid to be tested from a hydraulic liquid. This construction ensures the absence of dead space and a minimal test volume. The usefulness of the apparatus is demonstrated in the automated assay of protease, amylase and pectinase activity. Development of a mathematical model describing the enzymic degradation of macromolecules resulted in a reciprocal equation allowing rectilinear presentation of the calibration data. The feasibility of this model was tested by linear regression analysis of the data.

FILE 'HOME' ENTERED AT 15:57:29 ON 01 OCT 2002